Assessing monitoring methods for detection of potential leakage at carbon storage sites

Erika Gasperikova, LBNL

Contributors: Xianjin Yang (LLNL), Catherine Yonkofski (PNNL), Robert Dilmore (NETL)

Underground Injection Control Conference and NRAP Workshop, San Antonio, Texas February 19, 2020













- General considerations for geological carbon storage (GCS) site monitoring
- Monitoring design in context of uncertainty
- Estimating monitoring technology detection thresholds
- Design of effective and efficient monitoring





Uses of Monitoring at a GCS Site

- Site characterization
- Conformance evaluation
- Containment assurance storage accounting
- Secondary plume detection risk assessment/decision support
- (Groundwater) resource protection Class VI permit





Class VI wells – Criteria and Standards



The owner or operator of a Class VI well must prepare, maintain, and comply with a testing and monitoring plan to verify that the geologic sequestration project is operating as permitted and is not endangering USDWs. The requirement to maintain and implement an approved plan is directly enforceable regardless of whether the requirement is a condition of the permit. The testing and monitoring plan must be submitted with the permit application, for Director approval, and must include a description of how the owner or operator will meet the requirements of this section, including accessing sites for all necessary monitoring and testing during the life of the project. Testing and monitoring associated with geologic sequestration projects must, at a minimum, include:

(d) Periodic monitoring of the ground water quality and geochemical changes above the confining zone(s) that may be a result of carbon dioxide movement through the confining zone(s) or additional identified zones including:

(1) The location and number of monitoring wells based on specific information about the geologic sequestration project, including injection rate and volume, geology, the presence of artificial penetrations, and other factors; and

(2) The monitoring frequency and spatial distribution of monitoring wells based on baseline geochemical data that has been collected under §146.82(a)(6) and on any modeling results in the area of review evaluation required by §146.84(c).

(g) Testing and monitoring to track the extent of the carbon dioxide plume and the presence or absence of elevated pressure (e.g., the pressure front) by using:

(1) Direct methods in the injection zone(s); and,

(2) Indirect methods (e.g., seismic, electrical, gravity, or electromagnetic surveys and/or down-hole carbon dioxide detection tools), unless the Director determines, based on site-specific geology, that such methods are not appropriate;

40 CFR 146.90 (d), (g),(i), (j)

(i) Any additional monitoring, as required by the Director, necessary to support, upgrade, and improve computational modeling of the area of review evaluation required under §146.84(c) and to determine compliance with standards under §144.12 of this chapter;

(j) The owner or operator shall periodically review the testing and monitoring plan to incorporate monitoring data collected under this subpart, operational data collected under §146.88, and the most recent area of review reevaluation performed under §146.84(e). In no case shall the owner or operator review the testing and monitoring plan less often than once every five years. Based on this review, the owner or operator shall submit an amended testing

https://www.govinfo.gov/content/pkg/CFR-2019-title40-vol25/pdf/CFR-2019-title40-vol25-part146-subpartH.pdf









Pacific Northwest

<u>Monitoring – Spatial Resolution</u>

Remote, geophysical measurements



Approximate Spatial Resolution







EST. 1943



Geophysical Monitoring

Techniques are complementary, as each provides sensitivity that the other technique cannot provide





ABORATORY

BERKELEY LAB

NATIONAL LABORATORY

EST. 1943



Optimal Monitoring Design



Site specific, fit-for-purpose monitoring design







EST. 1943



Advanced Monitoring Systems











Pacific Northwest

NATIONAL LABORATORY

Pilot Projects

- Small injection volumes => can be used as analogs for secondary CO₂ plumes
- Verify model results
- Test new technologies
- Test monitoring designs



Otway: Time-lapse seismic signals

(Glubokovskikh, 2019)











Modeling of Geophysical Monitoring

Full spectrum of hypothetical scenarios including those that are highly unlikely

- Given: CO₂ migration through a well with uncertain characteristics (depth, size, saturation distribution)
- What is the probability of detecting secondary CO₂ plume for various monitoring technologies/deployment?













Approach

Full spectrum of hypothetical scenarios including those that are highly unlikely

- 1. Stochastic simulation of plumes
- 2. Model geophysical monitoring for all realizations
- 3. Evaluate the probability of detecting and time/mass of a secondary plume before detection
- 4. Assess acceptability of detectability (relative to resource protection and/or decision support)
- 5. Apply understanding of monitoring technology effectiveness in site-scale monitoring design





1. Stochastic simulation of plumes

Full spectrum of hypothetical scenarios including those that are highly unlikely











2. Model geophysical monitoring









Pacific Northwest

2. Model geophysical monitoring













3. Evaluate the probability of detection and time/mass of a secondary plume before detection









EST. 1943



4. Fit-for-purpose Survey Design – Detection Thresholds



ECHNOLOGY

BERKELEY LAB

ABORATORY

Los Alamos

EST.1943

Pacific Northwest

NATIONAL LABORATORY



4. Fit-for-purpose Survey Design – Time Intervals



rurri

BERKELEY LAB

ECHNOLOGY

ABORATORY

Los Alamos

NATIONAL LABORATORY

EST.1943

Pacific Northwest

NATIONAL LABORATORY



5. Risk-based site-scale monitoring design and optimization



unknown random leak location • known potential leak location • simulation (injection) well

proposed monitoring well



Known potential leakage pathways play a central role in designing the monitoring plans

Complementary spatial and time resolutions:

- **3D** seismic to identify high risk ۲ zone
- pressure monitoring more efficient detection in time
- groundwater and soil gas monitoring - to confirm the impact domain







cecee

BERKELEY LAE



Pacific Northwest NATIONAL LABORATORY

DREAM



ECHNOLOGY

BERKELEY LAE

ABORATORY

los Alamos

EST. 1943

Pacific Northwest

NATIONAL LABORATORY



FutureGen 2.0 Case Study (Illinois Basin)

UIC Class VI Permit Application





End of injection



50-years later













FutureGen 2.0 – Monitoring network

Original Monitoring Plan













FutureGen 2.0 – DREAM

INPUT

- NRAP-Open-IAM output (480 simulations)
- Sensors and detectability based on FutureGen
- Incrementally increasing budget; limited at 8 wells





- Effective and efficient monitoring network
- Configuration with the lowest time to detection of the plume

	Table A.5 & A.7 (FutureGen Industrial Alliance, 2013a)				NRAP-Open-IAM	
	Min	Max	Unit	Precision +/-	Indicator	Threshold
Pressure	0	2500	psi	0.065%	relative	0.00065
Temperature	0	150	F	0.03%	relative	0.0003
DIC	0.2		mg/L	20%	relative	0.2
pH	2	12	pН	0.2	absolute	0.2
TDS	10		mg/L	10%	relative	0.1











FutureGen 2.0 – DREAM - Time to detection





NATIONAL ENERGY TECHNOLOGY LABORATORY





- Optimal monitoring program utilizes both direct (pressure, temperature, fluid sampling) and indirect (geophysical) monitoring methods.
- Geophysical measurements produce proxies for saturation and mass that, when properly calibrated and interpreted, are robust quantitative estimates of these key storage parameters. Value of information (VOI) is expected to play a role in selection of monitoring tools.
- Site-specific cost/benefit approach to selecting post-injection monitoring techniques should be developed in association with a quantitative risk assessment.





This work was completed as part of National Risk Assessment Partnership (NRAP) project. Support for this project comes from the U.S. Department of Energy (DOE) Office of Fossil Energy's Crosscutting Research Program. Work at Lawrence Berkeley National Laboratory was completed under the U.S. DOE Contract No. DE-AC02-05CH1123. Work at National Energy Technology Laboratory was performed under Field Work Proposal No. 1022407. Work at Pacific Northwest National Laboratory was supported under the U.S. DOE Contract No. DE-AC05-76RL01830. The work by LLNL was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under contract DE-AC52-07NA27344, Lawrence Livermore National Security, LLC and this presentation was reviewed and released as LLNL-PRES-804186.



