On-farm implementation of onfarm Managed Aquifer Recharge

Groundwater Protection Council 7 March 2023

Michele L. Reba, PhD, PE

Delta Water Management Research Unit

Contributions from:

Dr. Deborah Leslie, University of Memphis

Allegra Pieri, Arkansas State University

Ian Godwin, Arkansas State University



Delta Water Management Research Unit

- Worksite 2011
- Established 2014
- Scientists
 - Dr. Arlene Adviento-Borbe
 - Dr. Joseph H Massey
- Collaboration
- Water resources
 - Quantity
 - Quality
 - Greenhouse gas emissions



Preserving water quantity and quality for agriculture in the Lowe.

Delta Water Management Focus Areas

Water Quality

Why?

- Agronomic cost
- Contribute to hypoxic zone

What?

- 9 Edge-of-field
- 10 in-stream
- Excess nutrients & sediment
- National networks




Water Quantity

Why?

- Decline in MRVA
- Cost of pumping from deeper

What?

- Irrigation (Massey)
- Automation (Massey)
- Managed Aquifer Recharge
- Surface Water



GHG Emissions


Why?


- Mitigation potential
- Environmental markets


What?

- CO₂, CH₄, N₂O
- 8 Eddy covariance towers
- Static vented chamber (AAB)
 - Gold standard









(AR Dept of Ag - Natural Resources Division, 2019)

DELTA WATER MANAGEMENT RESEARCH UNIT

Managed Aquifer Recharge

Managed Aquifer Recharge (MAR) is the efficient storage and recovery of water in aquifers Davis, CA

- Increase the amount of water returning to an aquifer
- Water scarcity driven
- Water quality constrained
- Ongoing USDA-ARS MAR research



Image source: Clinton Williams

Image source: Scott Bradford

DFI TA WATER

Methods of MAR in Arkansas

- Direct injection
 - USGS 1960s: air entrainment, clogging, chemistry
 - Drinking water standard
- Infiltration basins
 - Space
 - Leslie et al., 2022*
- Direct Injection
 - Water quality
- Infiltration galleries


*Leslie, D.L., M.L. Reba, and J.B. Czarnecki. Managed aquifer recharge using a borrow pit in connection with the Mississippi River Valley alluvial aquifer in northeastern Arkansas. *Journal of Soil and Water Conservation*. Accepted June 2022.





MAR Technique: Infiltration Galleries


• Infiltration Galleries - Trenches excavated to a permeable material, filled with gravel that recharge groundwater through internal plumbing connected to a water source




Site evaluation

- Confining unit thickness mapping
- Geophysical surveying
- Sampling surveying


Godwin, I., M.L. Reba, D. Leslie, R. Adams, and J. Rigby. Feasibility of Infiltration Galleries for Managed Aquifer Recharge in the Mississippi River Valley Alluvial Aquifer of Northeast Arkansas. *Agricultural Water Management*. Vol. 264, 107531. <u>https://doi.org/</u>10.1016/j.agwat.2022.107531. 2022.







Hydrogeology



- Surface confining clay unit
 - Rice growing
 - Limits natural recharge
- Upper unit: fine clay, silt, and sand
- Lower unit: coarse sands and gravels

Permission-ADEQ

- Producer interest
- Landowner permission
 - Lease agreement
- Documentation
 - ADEQ UIC Inventory Requirement for "Authorized by Rule" Class V Wells
- Reporting

- Permit included
 - Project Description
 - Monitoring planned
 - Maps of site
 - Adjacent land owners
 - Letter of support
 - Water quality data
 - Nearby wells
 - Geologic cross sections
 - Groundwater elevations

Study Area




Located northeast of Weiner, AR


Construction: October 2020 April 2021

Distribution System: October 2021 February 2022

Infiltration: February 10, 2022 Estimated excavation volume from gallery-end slopes: 21200 ft3 Estimated Total Volume Excavated: 63570 ft3 (2350 cy)

PLAN VIEW








DELTA WATER MANAGEMENT RESEARCH UNIT

Estimated excavation volume by dirt-pan: 975m3 (1275 cy) Estimated Volume by Excavator: 825m3 (1080 cy)




SIDE VIEW

Insert Video Here








Monitoring

- Gallery infiltration rates
 - Flow rates
 - Gallery monitoring port water levels
- Electrical resistivity tomography (ERT) surveys
 - An electrical current is introduced into the ground through two electrodes, and electrical resistivity at the surface is measured
- Water levels of on-site groundwater monitoring wells
- Water quality of reservoir water, lysimeters and on-site groundwater monitoring wells



Infiltration rates






DELTA WATER MANAGEMENT RESEARCH UNIT

Electrical resistivity surveys


- Black trapezoids represent the gravel fill of the infiltration galleries(drawn to scale)
- Survey 1-Pre-injection
- Survey 23-after injecting approximately 59,347 L (15,768 gal) of reservoir water during hour 17 of the first injection event
- Resistivity in the unsaturated zone was reduced by an order of magnitude as lower resistivity reservoir water was injected



Conclusions & Future Plans

- Managed aquifer recharge may be part of the solution to aquifer decline in the MRVAA
- Made strides to determine the utility of these systems but continue to test
- Simplify design
 - Dry wells
- Winter 2022-2023
 - 6 months of injection
 - Pulses of maximum flow
 - Water quality monitoring
- Modeling





Special Thanks To:

- USDA Besearch Service
- Landowners & Producers: Tom Wimpy, Sherry Hay & Terry Duffel
- USDA-ARS-DWMRU: Allegra Pieri, Ian Godwin, Yin-Lin Chiu, Dr. Joseph Massey, Dr. Teague, Patrick Dill, Geoffrey Payne, Brody Ridge, Anna Pieri, Thais Jardim, Trenton Barker, Jonathon Delp, Patrick Leppold, Cameron Green
- USDA-NRCS: Craig Roach, Tim Ferguson, Cory Perrin, Shawn Brewer, Chris King
- University of Memphis: Dr. Deborah Leslie, Alexandra Sharp
- USGS: Tim Kresse, Ryan Adams, Wade Kress, JR Rigby
- Arkansas State University: Dr. John Nowlin
- **P&P Consulting:** Richard Pickett
- MU Soil and Plant Testing Laboratory: Manjula Nathan











Thank you

Dr. Michele L. Reba Research Hydrologist Acting Research Leader USDA-ARS-Delta Water Management Research Unit <u>michele.reba@usda.gov</u>